



WOOD

This water-based coating for natural wood creates a weather-resistant surface without a sealant.

Surface Preparation	Ensure a clean surface before application. Wood may need to be sanded or pressure washed. Surface should be completely dry before application.
Application	Apply using pump or HVLP sprayer.
Dry Time	Less than 24 hours.
Cure Time	This coating completely adheres to the surface after 24 hours. The coating will only exhibit the hydrophobic property after this curing period.
Storage	2 year unopened shelf life stored at 38°F to 86°F (3°C to 30°C) out of sunlight in a dry, well-ventilated area.
Coverage	70-300 ml/10ft ² (1m ²) – highly dependent on porosity of the substrate.
Clean-Up & Removal	Pressure washing greater than 50 bar. The coating is only as sound as the substrate – anything that removes the top layer of the substrate will remove the coating.
Extended Care & Maintenance	Cleaning with water is recommended. Pressure resistant up to 50 bar. Remember, the coating is only as sound as the substrate.
Disposal	Follow local/federal/national regulations. Consult disposal experts and your regulatory agency for any questions.
First Aid	Eye Contact: Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. If symptoms persist, seek medical attention. Skin contact: Immediately rinse with water. Inhalation: If inhaled, remove to fresh air. Get medical attention if symptoms persist. Ingestion: Rinse mouth out, follow with drinking plenty of water. Do NOT induce vomiting; call for medical help immediately. If victim is vomiting, bring head in low position (increased danger of aspiration /perforation). A person vomiting while lying on their back should be turned onto their side.

KEEP OUT OF REACH OF CHILDREN

Emergency Telephone Number (U.S. & Canada): 1-800-535-5053

Emergency Telephone Number (Int'l): +1-352-323-3500