



PLASTIC & METALS PRODUCT DATA SHEET

OVERVIEW

Plastic & Metals is a coating that provides water and oil repelling properties to any non porous synthetic or metallic surface. This coating provides stain-resistance and easy-to-clean properties without affecting the appearance or texture of the substrate. Applied by simple spray and wipe application.

USES

- ▶ Iron
- ▶ Stainless steel
- ▶ Aluminum
- ▶ Brass
- ▶ Copper
- ▶ Polystyrene (PS)
- ▶ Polypropylene (PP)
- ▶ Polyethylene Terephthalate (PET/PETE)
- ▶ High-density Polyethylene (HDPE)
- ▶ Polyvinyl Chloride (PVC)

FEATURES

- ▶ Water-repellent
- ▶ Oil-repellent
- ▶ Easy-to-clean effect
- ▶ Invisible to the human eye (coating thickness: 100-150 nm)
- ▶ UV-stable
- ▶ Abrasion resistant
- ▶ Resistant to temperature change
- ▶ Breathable
- ▶ Simple application (do-it-yourself)
- ▶ Chemical resistant
- ▶ Dries in seconds, cures in 24 hours

APPLICATION AND STORAGE

Surface Preparation: Ensure a clean, dry surface before application.

Application: Spray and wipe with a clean paper towel, or cloth.

Dry/cure time: This coating completely adheres to the surface after 24 hours. The coating will only exhibit the hydrophobic property after this curing period.

Coverage: 10-15 mL/m²

Storage: 2 year unopened shelf life. (3°C to 30°C).

All statements, technical information and recommendations contained in this document are based upon tests or experience that DryWired believes are reliable. However, many factors beyond DryWired's control can affect the use and performance of a DryWired product in a particular application, including the conditions under which the product is stored or used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the DryWired product to determine whether it is fit for a particular purpose and suitable for the user's method of application. No warranty or condition, expressed or implied, is given regarding the accuracy of the statements, technical information or recommendations contained in this document. Except to the extent prohibited by law, DryWired will not be liable for any losses or damages arising in any way from the DryWired product including, without limitation, any direct, indirect, special, incidental or consequential damages, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



9606 S. SANTA MONICA BLVD. BEVERLY HILLS, CA 90210 | T: 323.581.8181 | F: 310.855.1208
WWW.DRYWIRED.COM