



## PERMA-CLEAN SOLAR 2.0 PRODUCT DATA SHEET

### OVERVIEW

DryWired® Perma-Clean Solar 2.0 is a transparent, single-step coating designed to increase the efficiency of solar panels. Perma-Clean Solar 2.0 alters the electrical resistance of a surface to give it antistatic and anti-soiling properties. In addition, the coating exhibits a hydrophilic, self-cleaning property that allows surface contaminants to be easily removed with only water. These properties not only allow for an increase in photovoltaic efficiency, but also reduce the amount of maintenance required.

### FEATURES

- ▶ Superhydrophilic
- ▶ Antistatic
- ▶ Self-cleaning
- ▶ Transparent
- ▶ Weather-resistant
- ▶ Strong adhesion to substrate
- ▶ Thickness: 100 nanometers
- ▶ Single-step application
- ▶ Cleans easily with water
- ▶ Reduce maintenance cycles

### APPLICATION AND STORAGE

**Surface Preparation:** Clean and dry surface. DO NOT apply in direct sunlight.

**Application:** Apply with squeegee. For more detailed instructions, reference *Perma-Clean Solar 2.0 Application Instructions*.

**Dry/cure time:** Dries in 2 minutes (@70°F/21°C), Cures in 14 days

**Coverage:** 10-20 g/m<sup>2</sup>

**Storage:** When stored according to recommended conditions on the safety data sheets, shelf life is six (6) months from date of manufacture. Once the 2 parts have been mixed, the solution will not last more than a couple of weeks depending on storage conditions. If the solution appears gel-like, it is no longer usable.

All statements, technical information and recommendations contained in this document are based upon tests or experience that DryWired believes are reliable. However, many factors beyond DryWired's control can affect the use and performance of a DryWired product in a particular application, including the conditions under which the product is stored or used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the DryWired product to determine whether it is fit for a particular purpose and suitable for the user's method of application. No warranty or condition, expressed or implied, is given regarding the accuracy of the statements, technical information or recommendations contained in this document. Except to the extent prohibited by law, DryWired will not be liable for any losses or damages arising in any way from the DryWired product including, without limitation, any direct, indirect, special, incidental or consequential damages, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.