



Safety Data Sheet

DryWired[®] Anti Graffiti

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: DryWired[®] Anti Graffiti
Recommended Use: Surface protection against graffiti for porous and non-porous building materials.
Supplier: DryWired[®]
Address: 5524 Alcoa Avenue
Vernon, CA 90058
Phone: 1-323-581-8181
Revised On: 11/09/16
Emergency Phone: US: 1-800-535-5053, International: 1-352-323-3500

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification: Not a hazardous substance or mixture.
GHS Label Elements: Not a hazardous substance or mixture.
Hazards Not Otherwise Identified: None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Trade Secret: Organic mixture in aqueous emulsion.
Chemical Characterization: Mixture.

SECTION 4: FIRST AID MEASURES

Description of first aid measures:

Eye Contact: Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. If symptoms persist, seek medical attention.

Skin Contact: Immediately rinse with water.

Inhalation: If inhaled, rinse mouth out and move to fresh air. Get medical attention if symptoms persist.

Ingestion: Rinse mouth out, follow with drinking plenty of water. If symptoms occur, seek immediate medical assistance.

Most important symptoms and effects, both acute and delayed: The most important known symptoms and effects are described in the labeling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment required: No further information available.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use fire extinguishing agents suitable for the surrounding area.

Special hazards arising from the substance or mixture: Thermal decomposition can lead to release of gasses/vapours.

Advice for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.

Further information: No further relevant information available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment.

Environmental precautions: Do not allow product to reach sewage systems, watercourse or penetrate ground/soil.

Methods and materials for containment and cleaning up: Absorb with liquid binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles. Refer to Section 7 for safe handling, Section 8 for personal protective equipment; refer to Section 13 for disposal information.

SECTION 7: HANDLINGS AND STORAGE

Precautions for safe handling: Ensure adequate ventilation. Handle in accordance with good industrial hygiene practices.

Conditions for safe storage: Keep container tightly closed. Keep from freezing.

Specific end use(s): No other uses other than specified in section 1.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters: No further relevant information available.

Engineering Controls: No further relevant information available.



Safety Data Sheet

DryWired® Anti Graffiti

Personal Protective Equipment:

Eyes: Safety glasses. Avoid contact with eyes.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

Skin: Wear gloves if necessary.

Respiratory protection: Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--|-------------------------------------|--|--------------------|
| Appearance: | White emulsion | Odour: | Characteristic |
| Odour Threshold: | No data available. | pH: | 4.0-10.0 at 20°C |
| Melting/Freezing Point: | No data available. | Initial Boiling Point/Range: | No data available. |
| Flash Point: | No data available. | Evaporation Rate: | No data available. |
| Flammability (solid, gas): | No data available. | Upper/Lower Flammability of Explosive Limits: | No data available. |
| Vapour Pressure: | No data available. | Vapour Density: | No data available. |
| Relative Density: | 0.94-0.96 g/cm ³ at 20°C | Solubility: | No data available. |
| Partition Coefficient: n-octanol & water: | No data available. | Auto-Ignition Temperature: | Not applicable. |
| Decomposition Temperature: | No data available. | Viscosity: | <200 mPas @ 20°C |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No data available. **Chemical stability:** Stable. **Possibility of hazardous reactions:** No reactions known.

Conditions to avoid: Heat, flames, sparks. **Incompatible materials:** No materials to be especially mentioned.

Hazardous decomposition products: No hazardous decomposition products if instructions for storage/handling are followed.

SECTION 11: TOXICOLOGICAL INFORMATION

On the skin: No irritant effect

On the eye: No irritant effect

Sensitization: No sensitizing affects known.

This product is not considered a carcinogen by IARC or NTP.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity, Bioaccumulative Potential, Persistence and Degradability, Mobility in Soil: No further relevant information.

Other adverse effects: Do not allow undiluted product of large quantities to reach ground water, water course, or sewage system- danger to drinking water is possible.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Methods: Small quantities can be disposed of with household waste.

Uncleaned Packaging: Recommendation: Dispose of as unused product according to official regulations.

SECTION 14: TRANSPORT INFORMATION

Not classified as a dangerous good.

SECTION 15: REGULATORY INFORMATION

Chemical Inventories: Not classified as a dangerous good. The components of this product are in compliance with the chemical notification requirements of TSCA. Contact DryWired® for more information.

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. DRYWIRED® MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.

User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application.

Given the variety of factors that can affect the use and application of a DryWired® product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the DryWired® product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.