

## Product Description

DryWired® Anti Graffiti is a paraffin wax emulsion infused with silicon dioxide nanotechnology that creates an invisible, impenetrable sacrificial barrier. Anti-Graffiti provides a cost-effective and environmentally safe option for protecting porous and painted surfaces from vandalism. For removal of graffiti, only hot water is needed, eliminating the use of toxic solvents. Additionally, the coating increases longevity of porous and painted surfaces by providing protection against moisture, humidity and weathering without breaking down due to extreme temperatures or exposure to UV light.

## Intended Uses

Porous or painted surfaces including:

- Natural stone
- Artificial stone
- Concrete
- Cinder blocks
- Ceramics
- Plaster
- Bricks
- Limestone
- Sandstone

## Features

- Water-repellent
- Oil-repellent
- Transparent
- Protects against UV damage
- Protects against weather damage
- Freeze/Thaw protection
- Non-stick characteristic
- Simple application (do-it-yourself)
- Prevents penetration of water and oil based paints
- Removal with only hot water
- Nonflammable

## Application

<b>Surface Preparation</b>	Ensure a clean, dry surface – pressure washing may be necessary. Any loose debris should be removed and imperfections should be repaired. The coating is only as sound as the substrate.
<b>Application</b>	Brush, roller, or spray. For porous surfaces, use product as supplied. For smooth surfaces, the product can be diluted up to 50% with water.
<b>Dry Time</b>	2-12 hours, highly dependent on temperature and humidity
<b>Coverage</b>	1 Gallon covers 320 ft <sup>2</sup> (30 m <sup>2</sup> ) – dependent on absorbency of the substrate.
<b>Removal</b>	Hot water over 70°C (158°F) must be used to remove graffiti. A pressure washer is recommended, though other tools can be used in combination with hot water for removal. Only hot water is needed for removal of the coating and graffiti. No solvents or chemical removers are necessary.
<b>Reapplication</b>	Once the graffiti and coating has been removed, let the surface dry completely. Once dry, reapply according to instructions above.

## Safety, Handling & Storage

When stored under conditions between 38°F - 86°F (3°C - 30°C) in the original, unopened container, the shelf life is two years. Before using this product, please read the current product Material Safety Data Sheet (available through your sales representative or at [www.DryWired.com](http://www.DryWired.com)) and the precautionary statement on the product package. Follow all applicable precautions and directions.

## Physical Properties

Property	Solution
Appearance	White emulsion
Solvent	Water
Odor	Characteristic
Density	0.95±.1g/cm <sup>3</sup> at 20°C
Boiling point of solvent	>100°C
Flashpoint	None
System	1-part
pH	4.0 - 10.0 at 20°C
Viscosity	<200 mPas @ 20°C

Property	Coating
Appearance	Transparent
Contact angle (static, water)	Hydrophobic
Contact angle (static, oil)	Oleophobic

## Packaging

Anti-Graffiti is available in:

- 3 kg Container
- Pallet (300, 3kg containers)

## Additional Information

To request additional product information or sales assistance, contact DryWired at 1-800-581-4528 or visit [www.drywired.com](http://www.drywired.com).

All statements, technical information and recommendations contained in this document are based upon tests or experience that DryWired believes are reliable. However, many factors beyond DryWired's control can affect the use and performance of a DryWired product in a particular application, including the conditions under which the product is stored or used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the DryWired product to determine whether it is fit for a particular purpose and suitable for the user's method of application. No warranty or condition, expressed or implied, is given regarding the accuracy of the statements, technical information or recommendations contained in this document. Except to the extent prohibited by law, DryWired will not be liable for any losses or damages arising in any way from the DryWired product including, without limitation, any direct, indirect, special, incidental or consequential damages, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



**US HEADQUARTERS**  
9606 S. Santa Monica Blvd. PH  
Beverly Hills, CA 90210

Please recycle. Printed in U.S.A.  
© Drywired 2019. All Rights Reserved.  
T: +1.800.581.4528 | [www.drywired.com](http://www.drywired.com)